

# Product Datasheet

Item No.: 10829

PRODUCT NAME

## Thermoplastic cable reel with PRCD 30 mA plug 40 m H07RN-F 3G1,5 IP44



- Rated residual current 30 mA
- Undervoltage release
- Trigger time less than 30 ms
- IP44: protected against foreign bodies and splash-proof
- Reel body made from robust, shatterproof special plastic
- With stable, shock-absorbing and galvanized single-foot frame with parking brake
- Frame with ergonomically shaped handle and patented cable guide
- With built-in thermal circuit breaker
- With function display and trip test button and electronic measuring instrument
- With PRCD shock-proof plug
- With 3 shock-proof socket outlets, splash-proof
- 230 V, 16 A, max. 3,500 W

Reference image

### Technical data

|                                  |                                                                                    |
|----------------------------------|------------------------------------------------------------------------------------|
| EAN                              | 4011160108297                                                                      |
| Weight [kg]                      | 7.35                                                                               |
| Dimensions                       | 19x38x28 cm                                                                        |
| Main color                       | black                                                                              |
| Series                           | PRCD                                                                               |
| Category                         | Personal protection range                                                          |
| Subcategory                      | PRCD range                                                                         |
| Cable type                       | H07RN-F                                                                            |
| Cross section [mm <sup>2</sup> ] | 3G1,5                                                                              |
| Cable color                      | black                                                                              |
| Cable length [m]                 | 40                                                                                 |
| Rated voltage [V]                | 230                                                                                |
| Rated current [A]                | 16                                                                                 |
| Maximum power                    | 3500 W                                                                             |
| Drum diameter                    | 285 mmØ                                                                            |
| Thermal fuse                     | 1P                                                                                 |
| IP protection                    | IP44                                                                               |
| Protection device                | PRCD shock-proof plug, 30 mA (art. no. 45209)                                      |
| Input                            | Shock-proof PRCD 30 mA plug 230 V, 16 A, IP44                                      |
| Output                           | 3x shock-proof connector with red protective cap, socket insert, 230 V, 16 A, IP44 |
| Total number of sockets          | 3                                                                                  |
| Number of Type F sockets (230 V) | 3                                                                                  |
| Number of cores                  | 3                                                                                  |
| mA                               | 30                                                                                 |

Your partner for professional lighting and electrical products.