Product Datasheet



PRODUCT NAME

Socket Tower 12-way with induction charging surface and 3x USB 2 m H05VV-F **3G1,5 BK IP20**











- 5 W charging surface for charging induction-compatible cell phones
- With illuminated switches for switching the shock-proof socket outlets on/off (4 sockets each per level)
- 2 m PVC cable H05VV-F 3G1.5 with shock-proof angle plug
- With increased touch protection and with overload protection
- 230 V~ / 16 A / 50-60 Hz / max. 3500 W
- IP20: for indoor use
- 12x shock-proof socket outlets 230 V / 16 A
- 3x USB sockets 5 V / 2.4 A
- With 3 illuminated switches

Reference image

Technical data

recinical data	
EAN	4011160182228
Weight [kg]	1.1
Dimensions	15x21,5x15 cm
Main color	black
Category	House and garden
Subcategory	Table socket outlets
Cable type	H05VV-F
Cross section [mm²]	3G1,5
Cable color	black
Cable length [m]	2
Rated voltage [V]	230
Rated current [A]	16
Maximum power	3500 W
IP protection	IP20
Input	Shock-proof angle plug 230 V, 16 A, IP20
Output	12x shock-proof connector 230 V, 16 A, IP20 3x USB socket 5 V / 2.4 A 3x illuminated switch With induction charging surface 5 W
Total number of sockets	15
Number of Type F sockets (230 V)	12
Number of USB ports	3

