

# Product Datasheet

Item No.: 19862

PRODUCT NAME

## EnergyTube XL Set 500 W with Profi tripod XXL 4,6 m - 70000 lm



Reference image



### EnergyTube XL 360° LED Floodlight 500 W (Art. No. 46242) in protective bag

- Designed for uniform illumination of large areas up to approx. 3200 m<sup>2</sup>
- Luminous flux: approx. 70,000 lm
- Colour temperature: 5000 K (neutral white)
- DIN spigot mount for use with tripods featuring DIN connection
- Alternatively, quick hanging via eyelet and carabiner hook
- LED enclosed in polycarbonate protection column – extremely impact-resistant (IK10)
- High-performance LEDs with a lifespan of over 50,000 hours (140 lm/W)
- Colour rendering index CRI > 80
- Beam angle: 360°
- 7 m rubber cable H07RN-F 3G1.5 with Schuko plug
- Integrated thermal protection
- Operating temperature range: -15°C to +40°C
- Power supply: 230 V / 50–60 Hz
- Protection rating: IP44 – protected against solid objects and splashing water

### Professional XXL Tripod with crossbar (Art. No. 46758)

- Powder-coated steel tube frame with 5 adjustable segments, supplied in a practical carrying bag
- Tripod with DIN spigot and 820 mm crossbar with DIN mount for quick attachment of work lights
- Legs with spikes for excellent stability, each telescopically adjustable
- Includes 3 safety ropes with carabiners and 3 ground pegs for stability
- Adjustable height: 1.3 m – 4.6 m
- Maximum load capacity: 40 kg

### Technical data

EAN	4011160198625
Weight [kg]	22.2
Dimensions	22,5x91x22,5 cm + 20x23,5x115 cm
Main color	blue
Series	EnergyLine
Category	Lighting
Subcategory	EnergyTube XL 360° LED Floodlight
Cable type	H07RN-F
Cross section [mm <sup>2</sup> ]	3G1,5
Cable color	black
Cable length [m]	7
Rated voltage [V]	230
Rated current [A]	16
Power [W]	500
IP protection	IP44
Input	Shock-proof plug 230 V, 16 A, IP44 with 7 m H07RN-F 3G1,5
Light color [K]	5000
Luminous flux [lm]	70000
Beam angle	360

Your partner for professional lighting and electrical products.