

Product Datasheet

Item No.: 20753

PRODUCT NAME

Solid rubber armored cable reel 30 m H07BQ-F 5G2,5 IP54



Reference image



- Reel bodies made from extremely durable vulcanized hard rubber material
- Impact-resistant, resistant to oil, grease and petrol, very good insulating properties, unbreakable
- With extremely stable double-tube frame made from 22-mm-thick steel tubing with parking brake
- 2 large crank handles, one of which rotates for easy winding in
- Frame with ergonomic non-slip carry handle and cable guide
- With built-in thermal circuit breaker
- With phase monitoring display
- Cable with polyurethane outer sheath for maximum mechanical stress, extremely weather-resistant, highly flexible, tear-resistant, cut-resistant and abrasion-resistant, in orange safety color
- IP54: protected against dust and splash-proof
- With CEE plug 400 V, 16 A, 5-pole
- With 2 shock-proof socket outlets 230 V, splash-proof and 1 CEE socket 400 V, 16 A, 5-pole
- CEE 400 V, 16 A, 5-pole, max. 10,000 W

Technical data

EAN	4011160207532
Weight [kg]	12
Dimensions	31,5x29x37 cm
Main color	black
Category	Cable reels
Subcategory	Solid rubber armoured cable reels
Cable type	H07BQ-F
Cross section [mm²]	5G2,5
Cable color	orange
Cable length [m]	30
Rated voltage [V]	400
Rated current [A]	16
Maximum power	11 kW
Brake	Yes
Drum diameter	290 mmØ
Metal frame	Yes
Thermal fuse	3P
IP protection	IP54
Input	CEE plug 400 V, 16 A, 5-pole with 30 m H07BQ-F 5G2.5
Output	2x shock-proof socket outlet 230 V, 16 A, IP54 1x CEE socket 400 V, 16 A, 5-pole Phase display L1, L2, L3
Total number of sockets	3
Number of Type F sockets (230 V)	2
Number of CEE 400 V 16 A sockets	1
Number of cores	5

Your partner for professional lighting and electrical products.