Product Datasheet Item No.: 22620



Xperts plastic empty reel, 3 shock-proof socket outlets, with USB, thermal switch, 285 mm





- 3 shock-proof socket outlets, with USB, thermal switch
- IP44
- 285 mm dia.
- For approx. 40 m cable

Reference image

Technical data

Weight [kg]2.15Dimensions22x39,7x31,2 cmMain colorblackSeriesXpertsCategoryCable reelsSubcategoryEmpty ReelsRated voltage [V]230Rated current [A]16Maximum power3500 WBrakeYesDrum diameter285 mmØMetal frameYesThermal fuse1PIP protectionIP44Output3x shock-proof connector with blue protective cap, socket insert, 230 V, 16 A, IP44Total number of sockets3	iecinical data	
Dimensions 22x39,7x31,2 cm Main color black Series Xperts Category Cable reels Subcategory Empty Reels Rated voltage [V] 230 Rated current [A] 16 Maximum power 3500 W Brake Yes Drum diameter 285 mmØ Metal frame Yes Thermal fuse 1P IP protection IP44 Output 3x shock-proof connector with blue protective cap, socket insert, 230 V, 16 A, IP44 Total number of sockets 3	EAN	4011160226205
Main color Series Xperts Category Cable reels Subcategory Empty Reels Rated voltage [V] 230 Rated current [A] 16 Maximum power 3500 W Brake Ves Drum diameter 285 mmØ Metal frame Yes Thermal fuse IP protection IP44 Output Total number of sockets Xperts Xperts Cable reels Axperts Axpert	Weight [kg]	2.15
SeriesXpertsCategoryCable reelsSubcategoryEmpty ReelsRated voltage [V]230Rated current [A]16Maximum power3500 WBrakeYesDrum diameter285 mmØMetal frameYesThermal fuse1PIP protectionIP44Output3x shock-proof connector with blue protective cap, socket insert, 230 V, 16 A, IP44Total number of sockets3	Dimensions	22x39,7x31,2 cm
Cable reels Subcategory Empty Reels Rated voltage [V] Rated current [A] Brake Yes Drum diameter Yes Thermal fuse IP protection Utyput Total number of sockets Cable reels Empty Reels Empty Reels Empty Reels 230 Annual Cable reels 240 Annual	Main color	black
Subcategory Empty Reels Rated voltage [V] 230 Rated current [A] 16 Maximum power 3500 W Brake Yes Drum diameter 285 mmØ Metal frame Yes Thermal fuse 1P IP protection IP44 Output 3x shock-proof connector with blue protective cap, socket insert, 230 V, 16 A, IP44 Total number of sockets 3	Series	Xperts
Rated voltage [V] 230 Rated current [A] 16 Maximum power 3500 W Brake Yes Drum diameter 285 mmØ Metal frame Yes Thermal fuse 1P IP protection IP44 Output 3x shock-proof connector with blue protective cap, socket insert, 230 V, 16 A, IP44 Total number of sockets 3	Category	Cable reels
Rated current [A] 16 Maximum power 3500 W Brake Yes Drum diameter 285 mmØ Metal frame Yes Thermal fuse 1P IP protection IP44 Output 3x shock-proof connector with blue protective cap, socket insert, 230 V, 16 A, IP44 Total number of sockets 3	Subcategory	Empty Reels
Maximum power 3500 W Brake Yes Drum diameter 285 mmØ Metal frame Yes Thermal fuse 1P IP protection IP44 Output 3x shock-proof connector with blue protective cap, socket insert, 230 V, 16 A, IP44 Total number of sockets 3	Rated voltage [V]	230
Brake Yes Drum diameter 285 mmØ Metal frame Yes Thermal fuse 1P IP protection IP44 Output 3x shock-proof connector with blue protective cap, socket insert, 230 V, 16 A, IP44 Total number of sockets 3	Rated current [A]	16
Drum diameter 285 mmØ Metal frame Yes Thermal fuse 1P IP protection IP44 Output 3x shock-proof connector with blue protective cap, socket insert, 230 V, 16 A, IP44 Total number of sockets 3	Maximum power	3500 W
Metal frame Yes Thermal fuse 1P IP protection IP44 Output 3x shock-proof connector with blue protective cap, socket insert, 230 V, 16 A, IP44 Total number of sockets 3	Brake	Yes
Thermal fuse 1P IP protection IP44 Output 3x shock-proof connector with blue protective cap, socket insert, 230 V, 16 A, IP44 Total number of sockets 3	Drum diameter	285 mmØ
IP protection IP44 Output 3x shock-proof connector with blue protective cap, socket insert, 230 V, 16 A, IP44 Total number of sockets 3	Metal frame	Yes
Output 3x shock-proof connector with blue protective cap, socket insert, 230 V, 16 A, IP44 Total number of sockets 3	Thermal fuse	1P
Total number of sockets 3	IP protection	IP44
	Output	3x shock-proof connector with blue protective cap, socket insert, 230 V, 16 A, IP44
Number of Type F sockets (230 V) 3	Total number of sockets	3
	Number of Type F sockets (230 V)	3

