


Product Datasheet

Item No.: 38604

PRODUCT NAME

5-way socket outlet with PRCD plug 4,5 m H07RN-F 3G1,5 BK IP44



- Rated residual current 30 mA
- Undervoltage release
- Trigger time less than 30 ms
- IP44: protected against foreign bodies and splash-proof
- With safety flap lips and illuminated on/off switch
- Power cord with RCD for reliable protection against residual current
- Very sturdy design
- 230 V, 16 A, max. 3,500 W

Reference image

Technical data

EAN	4011160386046
Weight [kg]	1.2
Dimensions	10x6x40 cm
Main color	black
Series	PRCD
Category	Personal protection range
Subcategory	PRCD range
Cable type	H07RN-F
Cross section [mm ²]	3G1,5
Cable color	black
Cable length [m]	4.5
Rated voltage [V]	230
Rated current [A]	16
Maximum power	3500 W
IP protection	IP44
Protection device	PRCD shock-proof plug, 30 mA (art. no. 45209)
Input	Shock-proof PRCD 30 mA plug 230 V, 16 A, IP44
Output	5x shock-proof connector with blue protective cap, with on/off switch 230 V, 16 A, IP44
Total number of sockets	5
Number of Type F sockets (230 V)	5
mA	30

Your partner for professional lighting and electrical products.