## **Product Datasheet**

Item No.: 42832



PRODUCT NAME

## INDU 3 Charging station with two 10 W chargers, LED battery-operated floodlight and LED battery-operated handlamp - 1000 lm















- Charging stations with one 10 watt charger (INDU 1) or with two 10 watt chargers (INDU 3)
- Housing with very strong magnetic back suitable for mounting on metallic surfaces or with drill holes for wall mounting.
- Magnets on the front secure the floodlight and/or handlamp to the charging station during charging.
- Additional fold-out compartment for charging induction-compatible cell phones.
- Incl. USB type C charging cable with USB 5V DC 2A power plug
- IP20: for indoor use
- Switch with four lighting levels: Spotlight/level 1: 250 lm; operating time ~4.5 h Level 2: 120 lm; operating time ~10 h Level 3: 350 lm; operating time ~4.5 h Level 4: 670 lm; operating time ~2.5 h
- Color temperature 6500 kelvin
- 3.7 V / 2600 mAh Li-ion battery / 18650
- Charging time via USB type C cable: ~4 h
- Charging time via induction: ~6 h
- With integrated battery status display
- 180° folding bracket with integrated magnets
- IP65: dust-tight and jet-water-proof
- Switch with four lighting levels: Level 1: 5 lm; operating time ~200 h Level
  2: 30 lm; operating time ~25 h Level 3: 400 lm; operating time ~4 h Level
  4: 1000 lm; operating time ~2 h
- Color temperature 6500 kelvin
- 3.7 V / 2600 mAh Li-ion battery / 18650
- Charging time via USB type C cable: ~4 h
- Charging time via induction: ~6 h
- With integrated battery status display
- IP68: dust-tight and water pressure tight

## **Technical data**

EAN	4011160428326
Weight [kg]	1.2
Dimensions	30x11x8,5 cm
Main color	blue
Category	Lighting
Subcategory	Induction lamps
Rated voltage [V]	230
Power [W]	10
IP protection	IP20
Light color [K]	6500
Luminous flux [lm]	1000

