

Product Datasheet

Item No.: 45222



PRODUCT NAME

PRCD extension 1-way, width PRCD personal protection switch 30 mA 3 m H07RN-F 3G1,5 IP44



Reference image



- Rated residual current 30 mA
- Undervoltage release
- Trigger time less than 30 ms
- IP44: protected against foreign bodies and splash-proof
- With shock-proof plug and shock-proof connector with protective cap
- With function display and trip test button and electronic measuring instrument
- 230 V, 16 A, max. 3,500 W

Technical data

EAN	4011160452222
Weight [kg]	0.92
Dimensions	17x8x17 cm
Main color	black
Series	PRCD
Category	Personal protection range
Subcategory	PRCD range
Cable type	H07RN-F
Cross section [mm²]	3G1,5
Cable color	black
Cable length [m]	3
Rated voltage [V]	230
Rated current [A]	16
Maximum power	3500 W
IP protection	IP44
Protection device	PRCD inline RCD 30 mA IP66 (art. no. 45223)
Input	Shock-proof plug 230 V, 16 A, IP44
Output	1x shock-proof connector with protective cap 230 V, 16 A, IP44
Total number of sockets	1
Number of Type F sockets (230 V)	1
mA	30

Your partner for professional lighting and electrical products.

