

# Product Datasheet

Item No.: 46241

PRODUCT NAME

## EnergyTube XL 360° LED floodlight 200 W - 30000 lm



Reference image



- Premium 360° LED floodlight for all-round illumination of large areas
- With DIN pin attachment for mounting on tripods with DIN pin
- Possible use of metal eyelet and snap hook for quick hanging
- LED housed in polycarbonate protective column, extremely impact-resistant IK10
- Extremely long-lasting high-performance LEDs with a lifespan of over 50,000 hours
- Color rendering index: CRI > 80
- With integrated thermal switch
- Surrounding operating temperature: -15°C to +40°C
- Beam angle: 360°
- Connection: 230 V/50-60 Hz
- IP44: protected against foreign bodies and splash-proof

### Technical data

|                     |                                                           |
|---------------------|-----------------------------------------------------------|
| EAN                 | 4011160462412                                             |
| Weight [kg]         | 5.1                                                       |
| Dimensions          | 22,5x62x22,5 cm                                           |
| Main color          | blue                                                      |
| Series              | EnergyLine                                                |
| Category            | Lighting                                                  |
| Subcategory         | EnergyTube XL 360° LED Floodlight                         |
| Cable type          | H07RN-F                                                   |
| Cross section [mm²] | 3G1,5                                                     |
| Cable color         | black                                                     |
| Cable length [m]    | 7                                                         |
| Rated voltage [V]   | 230                                                       |
| Power [W]           | 200                                                       |
| IP protection       | IP44                                                      |
| Input               | Shock-proof plug 230 V, 16 A, IP44 with 7 m H07RN-F 3G1,5 |
| Light color [K]     | 5000                                                      |
| Luminous flux [lm]  | 30000                                                     |

Your partner for professional lighting and electrical products.