

# Product Datasheet

Item No.: 46325

PRODUCT NAME

## Optiline LED floodlight 50 W - 4500 lm



- LEDs with a lifespan of over 40,000 hours
- Color temperature: 4,000 K (neutral white)
- LED beam angle: 100°
- Slimline die-cast aluminum housing with swiveling and lockable fastening material
- Power cord and glass cannot be replaced
- Connection: 220-240 V/50 Hz
- With 1 m rubber power cable H05RN-F 3G1.0 without plug
- IP65: dust-tight and splash-proof

Reference image

### Technical data

|                     |                                                        |
|---------------------|--------------------------------------------------------|
| EAN                 | 4011160463259                                          |
| Weight [kg]         | 1.4                                                    |
| Dimensions          | 20,2x5,6x23 cm                                         |
| Main color          | black                                                  |
| Series              | Optiline                                               |
| Category            | Lighting                                               |
| Subcategory         | Optiline floodlight series                             |
| Cable type          | H05RN-F                                                |
| Cross section [mm²] | 3G1,0                                                  |
| Cable color         | black                                                  |
| Cable length [m]    | 1                                                      |
| Rated voltage [V]   | 230                                                    |
| Rated current [A]   | 16                                                     |
| Power [W]           | 50                                                     |
| IP protection       | IP65                                                   |
| Input               | With 1 m rubber power cable H05RN-F 3G1,0 without plug |
| Light color [K]     | 4000                                                   |
| Luminous flux [lm]  | 4500                                                   |

Your partner for professional lighting and electrical products.