

Product Datasheet

Item No.: 46344



PRODUCT NAME

Optiline mobile LED floodlight 24 W - 2500 lm



Reference image



- LEDs with a lifespan of over 40,000 hours
- Color temperature: 4,000 K (neutral white)
- LED beam angle: 100°
- Color rendering index: CRI > 80
- With polycarbonate diffuser plate
- Extremely slimline floodlight housing made of special plastic and lockable fixing holder
- Power cord and diffuser plate cannot be replaced
- Connection: 220-240 V/50 Hz
- 3 m heavy-duty rubber cable H07RN-F 3G1.5 with shock-proof plug
- IP54: protected against dust and splash-proof

Technical data

EAN	4011160463440
Weight [kg]	1.54
Dimensions	10x24,8x31 cm
Main color	blue
Series	Optiline
Category	Lighting
Subcategory	Optiline floodlight series
Cable type	H07RN-F
Cross section [mm²]	3G1,5
Cable color	black
Cable length [m]	3
Rated voltage [V]	230
Rated current [A]	16
Power [W]	24
IP protection	IP54
Input	Shock-proof plug 230 V, 16 A, IP44 with 3 m H07RN-F 3G1,5
Output	1x shock-proof connector with protective cap 230 V, 16 A, IP44
Light color [K]	4000
Luminous flux [lm]	2500
Total number of sockets	1
Number of Type F sockets (230 V)	1

Your partner for professional lighting and electrical products.

