

Product Datasheet

Item No.: 46347

PRODUCT NAME

Optiline LED floodlight on tripod 2 x 30 W - 6500 lm



Reference image



- LEDs with a lifespan of over 40,000 hours
- Color temperature: 4,000 K (neutral white)
- LED beam angle: 100°
- Color rendering index: CRI > 80
- With polycarbonate diffuser plate
- Extremely slimline floodlight housing made of special plastic and lockable fixing holder
- Power cord and diffuser plate cannot be replaced
- Connection: 220-240 V/50 Hz
- Robust, powder-coated tripod, space-saving collapsible design
- Span of tripod: 1.3 m
- Height adjustable from 1.2_x001E_m to 1.6_x001E_m including floodlight
- With 3 m rubber power cable H05RN-F 3G1.0 with shock-proof plug
- IP54: protected against dust and splash-proof

Technical data

EAN	4011160463471
Weight [kg]	6.2
Dimensions	20x88,5x26 cm
Main color	blue
Category	Lighting
Subcategory	Optiline floodlight series
Cable type	H05RN-F
Cross section [mm ²]	3G1,0
Cable color	black
Cable length [m]	3
Rated voltage [V]	230
Rated current [A]	16
Power [W]	60
IP protection	IP54
Input	Shock-proof plug 230 V, 16 A, IP44 with 3 m H05RN-F 3G1.0
Light color [K]	4000
Luminous flux [lm]	6500

Your partner for professional lighting and electrical products.