

# Product Datasheet

Item No.: 46370

PRODUCT NAME

## 360° LED rotating beacon 70 W - 6000 lm



- Optimum light distribution thanks to 360° beam angle
- Color rendering index: CRI > 80
- Cylinder made of polycarbonate, extremely shock-resistant IK08
- Base made of plastic with handles and two shock-proof socket outlets with flap lids (230 V, 16 A, IP54)
- With non-slip feet for mobile use
- Folding hook for individual attachment to ceilings or scaffolding
- 3 m heavy-duty rubber cable H07RN-F 3G1.5 with shock-proof plug
- With on/off switch
- Diameter x height: 250 x 340 mm
- Weight: 3.2 kg
- Connection: 230 V / 16 A / max. 3500 W / 50-60 Hz
- IP54: protected against dust and splash-proof

Reference image

### Technical data

|                                  |                                                           |
|----------------------------------|-----------------------------------------------------------|
| EAN                              | 4011160463709                                             |
| Weight [kg]                      | 3.2                                                       |
| Dimensions                       | 32x25,5x34,5 cm                                           |
| Main color                       | black                                                     |
| Category                         | Lighting                                                  |
| Subcategory                      | 360° rotating beacon                                      |
| Cable type                       | H07RN-F                                                   |
| Cross section [mm <sup>2</sup> ] | 3G1,5                                                     |
| Cable color                      | black                                                     |
| Cable length [m]                 | 3                                                         |
| Rated voltage [V]                | 230                                                       |
| Rated current [A]                | 16                                                        |
| Power [W]                        | 70                                                        |
| IP protection                    | IP54                                                      |
| Input                            | Shock-proof plug 230 V, 16 A, IP44 with 3 m H07RN-F 3G1,5 |
| Light color [K]                  | 4000                                                      |
| Luminous flux [lm]               | 6000                                                      |
| Total number of sockets          | 2                                                         |

Your partner for professional lighting and electrical products.