

Product Datasheet

Item No.: 46372

PRODUCT NAME

Optiline 360° LED rotating beacon 30 W - 3200 lm



Reference image



- Optimum light distribution thanks to 360° beam angle
- Extremely long-lasting LEDs: Lifespan of over 30,000 hours (106 lm/W)
- Color rendering index: CRI > 80
- Housing made of ABS / diffuser made of PC
- Cylinder made of polycarbonate, extremely shock-resistant IK08
- 1 shock-proof socket outlet with flap lid (230 V, 16 A, IP54)
- With folding suspension hook on the bottom side
- With on/off switch
- Diameter x height: 200_x001E_x_x001E_220 mm
- With 3 m rubber power cable H07RN-F 3G1.5 with shock-proof plug
- Connection: 230 V / 16 A / max. 3500 W / 50-60 Hz
- IP54: protected against dust and splash-proof

Technical data

EAN	4011160463723
Weight [kg]	2.1
Dimensions	21x22,7x24 cm
Main color	black
Series	Optiline
Category	Lighting
Subcategory	360° rotating beacon
Cable type	H07RN-F
Cross section [mm²]	3G1,5
Cable color	black
Cable length [m]	3
Rated voltage [V]	230
Rated current [A]	16
Power [W]	30
IP protection	IP54
Input	Shock-proof plug 230 V, 16 A, IP44 with 3 m H07RN-F 3G1,5
Output	1x shock-proof connector with protective cap 230 V, 16 A, IP54
Light color [K]	4000
Luminous flux [lm]	3200
Total number of sockets	1
Number of Type F sockets (230 V)	1

Your partner for professional lighting and electrical products.