

Product Datasheet

Item No.: 46428

PRODUCT NAME

Slimline foldable CHIP LED floodlight 80 W - 6800 lm



Reference image



- Specially developed ORIGINAL SAMSUNG SMD LED: Lifespan of over 50,000 hours
- Reinforced die-cast aluminum housing in a modern design
- LED beam angle: 120°
- Connection: 230 V/50 - 60 Hz
- 3 m rubber power cable H07RN-F 3G1.5 with shock-proof plug
- Includes 2 shock-proof socket outlets with flap lids on the back
- IP44: protected against foreign bodies and splash-proof

Technical data

EAN	4011160464287
Weight [kg]	8.2
Dimensions	31x45,5x51 cm
Main color	blue
Series	Slimline
Category	Lighting
Subcategory	Slimline floodlight series
Cable type	H07RN-F
Cross section [mm ²]	3G1,5
Cable color	black
Cable length [m]	3
Rated voltage [V]	230
Rated current [A]	16
Power [W]	80
IP protection	IP44
Input	Shock-proof plug 230 V, 16 A, IP44 with 3 m H07RN-F 3G1,5
Output	2x shock-proof connector with protective cap 230 V, 16 A, IP44
Light color [K]	4000
Luminous flux [lm]	6800
Total number of sockets	2
Number of Type F sockets (230 V)	2
Beam angle	120

Your partner for professional lighting and electrical products.