

Product Datasheet

Item No.: 46670

PRODUCT NAME

Optiline LED floodlight 30 W with motion detector - 3600 lm IP44



- durable LEDs with a lifetime of over 40,000 hours
- slim plastic housing with aluminium heat dissipation plate
- frosted diffuser for even light distribution
- adjustable motion sensor (10 s – 10 min, 3–10,000 Lux, 4–10 m range)
- 15 cm rubber cable H07RN-F 3G1.5 with quick connector
- compatible cable cross-section: 3×2.5 mm²
- replaceable LED module
- energy efficiency class E
- protection rating IP44 – resistant to solid objects and splashing water

Reference image

Technical data

EAN	4011160466700
Weight [kg]	0.47
Dimensions	15,4x17,8x7,2 cm
Main color	black
Series	Optiline
Category	Lighting
Subcategory	Optiline floodlight series
Cable type	H07RN-F
Cross section [mm ²]	3G1,5
Cable color	black
Cable length [m]	0.15
Rated voltage [V]	230
Rated current [A]	16
Power [W]	30
IP protection	IP44
Input	15 cm H07RN-F 3G1.5 cable with quick connection adapter for cables up to 3G2,5
Light color [K]	4000
Luminous flux [lm]	3600
Beam angle	120

Your partner for professional lighting and electrical products.