

Product Datasheet

Item No.: 46680



PRODUCT NAME

Optiline mobile LED floodlight 30W - 3600 lm IP44



- Power: 30 W, luminous flux 3600 lm (120 lm/W)
- Colour temperature: 4000 K (neutral white)
- Durable plastic and aluminium housing
- Foldable handle for easy portability
- Protection rating IP44 – dust and splash resistant
- LED lifetime: over 40,000 hours

Reference image

Technical data

EAN	4011160466809
Weight [kg]	1.11
Dimensions	23x25,5x7 cm + Statyw
Main color	blue
Series	Optiline
Category	Lighting
Subcategory	Optiline floodlight series
Cable type	H07RN-F
Cross section [mm ²]	3G1,0
Cable color	black
Cable length [m]	2
Rated voltage [V]	230
Rated current [A]	16
Power [W]	30
IP protection	IP44
Input	Shock-proof plug 230 V, 16 A, IP44 with 2 m H05RN-F 3G1.0
Light color [K]	4000
Luminous flux [lm]	3600
Beam angle	120

Your partner for professional lighting and electrical products.



as – Schwabe GmbH Merkurstraße 10 D – 72184 Eutingen Tel. +49 7457 9 48 53 0 office@as-schwabe.de www.as-schwabe.com

Created 21.10.2025. All proprietary rights and the right to make technical changes are reserved. Reproduction is permitted only with the prior consent of as – Schwabe GmbH.