

# Product Datasheet

Item No.: 46714

PRODUCT NAME

## LED strip light reel 25 m 300 W - 37500 lm



- LED strip light on reel
- With stable, shock-absorbing and galvanized single-foot frame with parking brake and cable guide
- Version of the LED strip light: fluorescent
- Input: AC 230 V / 16 A
- Power: 12 W/m
- Luminous flux: 1,500 LM/m
- Color rendering index CRI: >80
- Beam angle: 120°
- LED lifespan: 30,000 hours
- Color temperature: 4,000 K
- High-quality LED
- Dimensions strip light (WxH): 18 x 8 mm
- Extendable up to 150 m total length
- IP65: dust-tight and protected against water jets

Reference image

### Technical data

|                     |                                                                      |
|---------------------|----------------------------------------------------------------------|
| EAN                 | 4011160467141                                                        |
| Weight [kg]         | 6.3                                                                  |
| Dimensions          | 19x38x28,5 cm                                                        |
| Main color          | red                                                                  |
| Category            | Lighting                                                             |
| Subcategory         | LED strip light                                                      |
| Cable type          | H05RN-F                                                              |
| Cross section [mm²] | 2x1,0                                                                |
| Cable color         | white                                                                |
| Cable length [m]    | 25                                                                   |
| Rated voltage [V]   | 230                                                                  |
| Rated current [A]   | 16                                                                   |
| Power [W]           | 300                                                                  |
| IP protection       | IP65                                                                 |
| Input               | Straight plug 2P/II, 2-pin, 230 V, 16 A, IP44 with 1,5 m H05RN-F 2x1 |
| Light color [K]     | 4000                                                                 |
| Luminous flux [lm]  | 37500                                                                |
| Beam angle          | 120                                                                  |

Your partner for professional lighting and electrical products.