

# Product Datasheet

Item No.: 46871



PRODUCT NAME

## Temporary LED Work Light 2 (mounted on OSB board, with 2P+G IP44 plug and socket, earthed) 24 W – 2700 lm



- Durable 24 W LED light with 2700 lm output (~113 lm/W)
- Impact-resistant housing – IK08
- Colour temperature: 4000 K (neutral white)
- Protection rating IP44 – protected against solid objects and splashing water
- Mounted on OSB board with hanging holes
- 4.5 m rubber cable H07RN-F 3G1.5 with 2P+Z IP44 plug 230 V/16 A
- 0.3 m cable with 2P+Z IP44 socket 230 V/16 A
- Suitable for outdoor use

Reference image

### Technical data

|                             |                                                                |
|-----------------------------|----------------------------------------------------------------|
| EAN                         | 4011160468711                                                  |
| Weight [kg]                 | 4,4                                                            |
| Dimensions                  | 118x25x7 cm                                                    |
| Main color                  | white                                                          |
| Category                    | Lighting                                                       |
| Subcategory                 | Handlamps and headlamps                                        |
| Cable type                  | H07RN-F                                                        |
| Cross section [mm²]         | 3G1,5                                                          |
| Cable color                 | black                                                          |
| Cable length [m]            | 4,5                                                            |
| Rated voltage [V]           | 230                                                            |
| Rated current [A]           | 16                                                             |
| Power [W]                   | 24                                                             |
| IP protection               | IP44                                                           |
| Input                       | Shock-proof plug 230 V, 16 A, IP44 with 4,5 m H07RN-F 3G1,5    |
| Output                      | 1x shock-proof connector with protective cap 230 V, 16 A, IP44 |
| Light color [K]             | 4000                                                           |
| Luminous flux [lm]          | 2700                                                           |
| Total number of sockets     | 1                                                              |
| Number of CEE 230 V sockets | 1                                                              |

Your partner for professional lighting and electrical products.

