

# Product Datasheet

Item No.: 59125



PRODUCT NAME

Construction site armored cable, extension with 1-way socket outlet 25 m  
H07BQ-F 3G1,5 OG IP44



- Approved for use on construction sites and in agricultural applications
- IP44: protected against foreign bodies and splash-proof
- Shock-proof plug and shock-proof connector with protective cap
- 230 V, 16 A

Reference image

### Technical data

|                                  |                                                                |
|----------------------------------|----------------------------------------------------------------|
| EAN                              | 4011160591259                                                  |
| Weight [kg]                      | 2.91                                                           |
| Dimensions                       | 26x8x26 cm                                                     |
| Main color                       | orange                                                         |
| Category                         | Extensions                                                     |
| Subcategory                      | For use on construction sites                                  |
| Cable type                       | H07BQ-F                                                        |
| Cross section [mm²]              | 3G1,5                                                          |
| Cable color                      | orange                                                         |
| Cable length [m]                 | 25                                                             |
| Rated voltage [V]                | 230                                                            |
| Rated current [A]                | 16                                                             |
| Maximum power                    | 3500 W                                                         |
| IP protection                    | IP44                                                           |
| Input                            | Shock-proof plug 230 V, 16 A, IP44                             |
| Output                           | 1x shock-proof connector with protective cap 230 V, 16 A, IP44 |
| Total number of sockets          | 1                                                              |
| Number of Type F sockets (230 V) | 1                                                              |
| Number of cores                  | 3                                                              |

Your partner for professional lighting and electrical products.

