Product Datasheet

Item No.: **59646**



PRODUCT NAME

CEE construction site extension with phase inverter 400 V, 32 A, 5P 10 m H07BQ-F 5G4















- IP44: protected against foreign bodies and splash-proof
- CEE plug and CEE connector with flap lid
- Latest generation "Made in Germany" plugs and connectors
- 400 V, 5-pole, 6 h

Reference image

Technical data

EAN 4011160596469 Weight [kg] 4.8 Dimensions 25x15x25 cm Main color orange Category CEE 400 V product range Subcategory CEE extensions Cable type H07BQ-F Cross section [mm²] 5G4 Cable color orange Cable length [m] 10 Rated voltage [V] 400 Rated current [A] 32 Maximum power 22 kW IP protection IP44 Input CEE plug with phase inverter 400 V, 32 A, 5-pole with 10 m H07BQ-F 5G4 Output 1x CEE socket 400 V, 32 A, 5-pole Total number of sockets 1 Number of CEE 400 V 32 A sockets 1	rechnical data	
Dimensions 25x15x25 cm Main color orange Category CEE 400 V product range Subcategory CEE extensions Cable type H07BQ-F Cross section [mm²] 5G4 Cable color orange Cable length [m] 10 Rated voltage [V] 400 Rated current [A] 32 Maximum power 22 kW IP protection IP44 Input CEE plug with phase inverter 400 V, 32 A, 5-pole with 10 m H07BQ-F 5G4 Output 1x CEE socket 400 V, 32 A, 5-pole Total number of sockets 1	EAN	4011160596469
Main colororangeCategoryCEE 400 V product rangeSubcategoryCEE extensionsCable typeH07BQ-FCross section [mm²]5G4Cable colororangeCable length [m]10Rated voltage [V]400Rated current [A]32Maximum power22 kWIP protectionIP44InputCEE plug with phase inverter 400 V, 32 A, 5-pole with 10 m H07BQ-F 5G4Output1x CEE socket 400 V, 32 A, 5-poleTotal number of sockets1	Weight [kg]	4.8
Category CEE 400 V product range Subcategory CEE extensions Cable type H07BQ-F Cross section [mm²] 5G4 Cable color orange Cable length [m] 10 Rated voltage [V] 400 Rated current [A] 32 Maximum power 22 kW IP protection IP44 Input CEE plug with phase inverter 400 V, 32 A, 5-pole with 10 m H07BQ-F 5G4 Output Total number of sockets 1	Dimensions	25x15x25 cm
Subcategory Cable type H07BQ-F Cross section [mm²] 5G4 Cable color orange Cable length [m] 10 Rated voltage [V] 400 Rated current [A] 32 Maximum power 22 kW IP protection IP44 Input CEE plug with phase inverter 400 V, 32 A, 5-pole with 10 m H07BQ-F 5G4 Output Total number of sockets 1	Main color	orange
Cable type H07BQ-F Cross section [mm²] 5G4 Cable color orange Cable length [m] 10 Rated voltage [V] 400 Rated current [A] 32 Maximum power 22 kW IP protection IP44 Input CEE plug with phase inverter 400 V, 32 A, 5-pole with 10 m H07BQ-F 5G4 Output 1x CEE socket 400 V, 32 A, 5-pole Total number of sockets 1	Category	CEE 400 V product range
Cross section [mm²] 5G4 Cable color orange Cable length [m] 10 Rated voltage [V] 400 Rated current [A] 32 Maximum power 22 kW IP protection IP44 Input CEE plug with phase inverter 400 V, 32 A, 5-pole with 10 m H07BQ-F 5G4 Output 1x CEE socket 400 V, 32 A, 5-pole Total number of sockets 1	Subcategory	CEE extensions
Cable color Cable length [m] 10 Rated voltage [V] 400 Rated current [A] 32 Maximum power 22 kW IP protection IP44 Input CEE plug with phase inverter 400 V, 32 A, 5-pole with 10 m H07BQ-F 5G4 Output Total number of sockets 1	Cable type	H07BQ-F
Cable length [m] 10 Rated voltage [V] 400 Rated current [A] 32 Maximum power 22 kW IP protection IP44 Input CEE plug with phase inverter 400 V, 32 A, 5-pole with 10 m H07BQ-F 5G4 Output 1x CEE socket 400 V, 32 A, 5-pole Total number of sockets 1	Cross section [mm ²]	5G4
Rated voltage [V] 400 Rated current [A] 32 Maximum power 22 kW IP protection IP44 Input CEE plug with phase inverter 400 V, 32 A, 5-pole with 10 m H07BQ-F 5G4 Output 1x CEE socket 400 V, 32 A, 5-pole Total number of sockets 1	Cable color	orange
Rated current [A]32Maximum power22 kWIP protectionIP44InputCEE plug with phase inverter 400 V, 32 A, 5-pole with 10 m H07BQ-F 5G4Output1x CEE socket 400 V, 32 A, 5-poleTotal number of sockets1	Cable length [m]	10
Maximum power22 kWIP protectionIP44InputCEE plug with phase inverter 400 V, 32 A, 5-pole with 10 m H07BQ-F 5G4Output1x CEE socket 400 V, 32 A, 5-poleTotal number of sockets1	Rated voltage [V]	400
IP protection IP44 Input CEE plug with phase inverter 400 V, 32 A, 5-pole with 10 m H07BQ-F 5G4 Output 1x CEE socket 400 V, 32 A, 5-pole Total number of sockets 1	Rated current [A]	32
Input CEE plug with phase inverter 400 V, 32 A, 5-pole with 10 m H07BQ-F 5G4 Output 1x CEE socket 400 V, 32 A, 5-pole Total number of sockets 1	Maximum power	22 kW
Output1x CEE socket 400 V, 32 A, 5-poleTotal number of sockets1	IP protection	IP44
Total number of sockets 1	Input	CEE plug with phase inverter 400 V, 32 A, 5-pole with 10 m H07BQ-F 5G4
	Output	1x CEE socket 400 V, 32 A, 5-pole
Number of CEE 400 V 32 A sockets 1	Total number of sockets	1
	Number of CEE 400 V 32 A sockets	1
Number of cores 5	Number of cores	5

