Product Datasheet

Item No.: 59648



PRODUCT NAME

CEE construction site extension with phase inverter 400 V, 32 A, 5P 50 m H07BQ-F 5G4















- IP44: protected against foreign bodies and splash-proof
- CEE plug and CEE connector with flap lid
- Latest generation "Made in Germany" plugs and connectors
- 400 V, 5-pole, 6 h

Reference image

Technical data

EAN 4011160596483 Weight [kg] 21.3 Dimensions 44x23x44 cm Main color orange Category CEE 400 V product range Subcategory CEE extensions Cable type H07BQ-F Cross section [mm²] 5G4 Cable color orange Cable length [m] 50 Rated voltage [V] 400 Rated current [A] 32 Maximum power 22 kW IP protection IP44 Input CEE plug with phase inverter 400 V, 32 A, 5-pole with 50 m H07BQ-F 5G4	recrimical data	
Dimensions 44x23x44 cm Main color orange Category CEE 400 V product range Subcategory CEE extensions Cable type H07BQ-F Cross section [mm²] 5G4 Cable color orange Cable length [m] 50 Rated voltage [V] 400 Rated current [A] 32 Maximum power 22 kW IP protection IP44	EAN	4011160596483
Main colororangeCategoryCEE 400 V product rangeSubcategoryCEE extensionsCable typeH07BQ-FCross section [mm²]5G4Cable colororangeCable length [m]50Rated voltage [V]400Rated current [A]32Maximum power22 kWIP protectionIP44	Weight [kg]	21.3
Category CEE 400 V product range Subcategory CEE extensions Cable type H07BQ-F Cross section [mm²] 5G4 Cable color orange Cable length [m] 50 Rated voltage [V] 400 Rated current [A] 32 Maximum power 1P protection IP44	Dimensions	44x23x44 cm
SubcategoryCEE extensionsCable typeH07BQ-FCross section [mm²]5G4Cable colororangeCable length [m]50Rated voltage [V]400Rated current [A]32Maximum power22 kWIP protectionIP44	Main color	orange
Cable type H07BQ-F Cross section [mm²] 5G4 Cable color orange Cable length [m] 50 Rated voltage [V] 400 Rated current [A] 32 Maximum power 22 kW IP protection IP44	Category	CEE 400 V product range
Cross section [mm²] 5G4 Cable color orange Cable length [m] 50 Rated voltage [V] 400 Rated current [A] 32 Maximum power 22 kW IP protection IP44	Subcategory	CEE extensions
Cable color orange Cable length [m] 50 Rated voltage [V] 400 Rated current [A] 32 Maximum power 22 kW IP protection IP44	Cable type	H07BQ-F
Cable length [m] 50 Rated voltage [V] 400 Rated current [A] 32 Maximum power 22 kW IP protection IP44	Cross section [mm²]	5G4
Rated voltage [V] 400 Rated current [A] 32 Maximum power 22 kW IP protection IP44	Cable color	orange
Rated current [A] 32 Maximum power 22 kW IP protection IP44	Cable length [m]	50
Maximum power 22 kW IP protection IP44	Rated voltage [V]	400
IP protection IP44	Rated current [A]	32
	Maximum power	22 kW
Input CEE plug with phase inverter 400 V, 32 A, 5-pole with 50 m H07BQ-F 5G4	IP protection	IP44
	Input	CEE plug with phase inverter 400 V, 32 A, 5-pole with 50 m H07BQ-F 5G4
Output 1x CEE socket 400 V, 32 A, 5-pole	Output	1x CEE socket 400 V, 32 A, 5-pole
Total number of sockets 1	Total number of sockets	1
Number of CEE 400 V 32 A sockets 1	Number of CEE 400 V 32 A sockets	1
Number of cores 5	Number of cores	5

