

# Product Datasheet

Item No.: 60555

PRODUCT NAME

## Portable solid rubber CEE construction site power combination unit M4, 22 kW



Reference image



- Extremely sturdy solid rubber housing, stackable for extremely space-saving storage
- Closed lower section of housing with 77 mm ground clearance to prevent water ingress
- Easy switching of the panel-mounted sockets
- Housing lid with stainless steel quick fastenings
- Touch-safe even when the lid is open – in accordance with BGV [German trade association provisions] A2
- Fuses are particularly well-protected due to their internal installation
- Additional safety can be achieved with an optional screw or padlock
- IP44: protected against foreign bodies and splash-proof

### Technical data

|                                  |                                                                                                                          |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| EAN                              | 4011160605550                                                                                                            |
| Weight [kg]                      | 9                                                                                                                        |
| Dimensions                       | 40x33x40 cm                                                                                                              |
| Main color                       | black                                                                                                                    |
| Category                         | CEE 400 V product range                                                                                                  |
| Subcategory                      | CEE construction site power combination unit series M                                                                    |
| Cable type                       | H07RN-F                                                                                                                  |
| Cross section [mm <sup>2</sup> ] | 5G6                                                                                                                      |
| Cable color                      | black                                                                                                                    |
| Cable length [m]                 | 2                                                                                                                        |
| Rated voltage [V]                | 400                                                                                                                      |
| Rated current [A]                | 16                                                                                                                       |
| Maximum power                    | 22 kW                                                                                                                    |
| IP protection                    | IP44                                                                                                                     |
| Protection device                | 1x RCD 40 A, 4-pole, 30 mA, type A<br>3x circuit breaker C 16 A, 1-pole<br>1x circuit breaker C 16 A, 3-pole             |
| Input                            | CEE plug 400 V, 32 A, 5-pole with 2 m H07RN-F 5G6                                                                        |
| Output                           | 3x shock-proof socket outlet 230 V, 16 A, IP44<br>2x CEE socket 400 V, 16 A, 5-pole<br>1x CEE socket 400 V, 32 A, 5-pole |
| Total number of sockets          | 6                                                                                                                        |
| Number of Type F sockets (230 V) | 3                                                                                                                        |
| Number of CEE 400 V 16 A sockets | 2                                                                                                                        |
| Number of CEE 400 V 32 A sockets | 1                                                                                                                        |

Your partner for professional lighting and electrical products.