Product Datasheet Item No.: 60813

PRODUCT NAME

Solid rubber multi socket outlet S11+, 2 m H07RN-F 5G6 22 kW





















- Housing made from extremely robust solid rubber
- Versions with various inputs and outputs for heavy-duty construction site
- IP44: protected against foreign bodies and splash-proof

Reference image

Technical data

EAN 4011160608131 Weight [kg] 5.3 Dimensions 25x13x54 cm Main color black Category CEE 400 V product range Subcategory CEE multi socket outlets series S Cable type H07RN-F Cross section [mm²] 5G6 Cable color black Cable length [m] 2 Rated voltage [V] 400 Rated current [A] 16 Maximum power 22 kW IP protection IP44 Protection device 1x MCB C 16 A, 3-pole [x MCB C 16 A, 1-pole] Input CEE plug 400 V, 32 A, 5-pole with 2 m H07RN-F 5G6 Output 3x shock-proof socket outlet 230 V, 16 A, IP44 [x EE socket 400 V, 32 A, 5-pole] Total number of sockets 5 Number of Type F sockets (230 V) 3 Number of CEE 400 V 16 A sockets 1 Number of CEE 400 V 16 A sockets 1	recillical data	
Dimensions 25x13x54 cm Main color black Category CEE 400 V product range Subcategory CEE multi socket outlets series S Cable type H07RN-F Cross section [mm²] 5G6 Cable color black Cable length [m] 2 Rated voltage [V] 400 Rated current [A] 16 Maximum power 22 kW IP protection IP44 Protection device 1x MCB C 16 A, 3-pole 1x MCB C 16 A, 1-pole Input CEE plug 400 V, 32 A, 5-pole with 2 m H07RN-F 5G6 Output 3x shock-proof socket outlet 230 V, 16 A, IP44 1x CEE socket 400 V, 16 A, 5-pole Total number of sockets 5 Number of Type F sockets (230 V) 3 Number of CEE 400 V 16 A sockets 1	EAN	4011160608131
Main color Category CEE 400 V product range Subcategory CEE multi socket outlets series S Cable type H07RN-F Cross section [mm²] 5G6 Cable color black Cable length [m] 2 Rated voltage [V] Ad00 Rated current [A] Maximum power 12 kW IP protection IP44 Protection device 1x MCB C 16 A, 3-pole 1x MCB C 16 A, 1-pole Input CEE plug 400 V, 32 A, 5-pole with 2 m H07RN-F 5G6 Output 3x shock-proof socket outlet 230 V, 16 A, IP44 1x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole	Weight [kg]	5.3
CategoryCEE 400 V product rangeSubcategoryCEE multi socket outlets series SCable typeH07RN-FCross section [mm²]5G6Cable colorblackCable length [m]2Rated voltage [V]400Rated current [A]16Maximum power22 kWIP protectionIP44Protection device1x MCB C 16 A, 3-pole 1x MCB C 16 A, 1-poleInputCEE plug 400 V, 32 A, 5-pole with 2 m H07RN-F 5G6Output3x shock-proof socket outlet 230 V, 16 A, IP44 1x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 1x CEE 400 V 16 A socketsNumber of Type F sockets (230 V)3Number of CEE 400 V 16 A sockets1	Dimensions	25x13x54 cm
Subcategory CEE multi socket outlets series S Cable type H07RN-F Cross section [mm²] 5G6 Cable color black Cable length [m] 2 Rated voltage [V] 400 Rated current [A] 16 Maximum power 22 kW IP protection IP44 Protection device 1x MCB C 16 A, 3-pole 1x MCB C 16 A, 1-pole Input CEE plug 400 V, 32 A, 5-pole with 2 m H07RN-F 5G6 Output 3x shock-proof socket outlet 230 V, 16 A, IP44 1x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole	Main color	black
Cable type	Category	CEE 400 V product range
Cross section [mm²]5G6Cable colorblackCable length [m]2Rated voltage [V]400Rated current [A]16Maximum power22 kWIP protectionIP44Protection device1x MCB C 16 A, 3-pole 1x MCB C 16 A, 1-poleInputCEE plug 400 V, 32 A, 5-pole with 2 m H07RN-F 5G6Output3x shock-proof socket outlet 230 V, 16 A, IP44 1x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-poleTotal number of sockets5Number of Type F sockets (230 V)3Number of CEE 400 V 16 A sockets1	Subcategory	CEE multi socket outlets series S
Cable color Cable length [m] 2 Rated voltage [V] 400 Rated current [A] 16 Maximum power 22 kW IP protection IP44 Protection device 1x MCB C 16 A, 3-pole 1x MCB C 16 A, 1-pole Input CEE plug 400 V, 32 A, 5-pole with 2 m H07RN-F 5G6 Output 3x shock-proof socket outlet 230 V, 16 A, IP44 1x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 5x CEE plug 400 V, 32 A, 5-pole 5x CEE socket 400 V, 16 A, IP44 1x CEE socket 400 V, 16 A, 5-pole 7x CEE socket 400 V, 32 A, 5-pole 5x CEE 400 V 16 A sockets 5x	Cable type	H07RN-F
Cable length [m] 2 Rated voltage [V] 400 Rated current [A] 16 Maximum power 22 kW IP protection IP44 Protection device 1x MCB C 16 A, 3-pole 1x MCB C 16 A, 1-pole Input CEE plug 400 V, 32 A, 5-pole with 2 m H07RN-F 5G6 Output 3x shock-proof socket outlet 230 V, 16 A, IP44 1x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 5x CEE plug 400 V, 32 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 5x CEE plug 400 V, 32 A, 5-pole 5x CEE socket 400 V, 32 A, 5-pole 5x CEE so	Cross section [mm²]	5G6
Rated current [A] 16 Maximum power 22 kW IP protection IP44 Protection device 1x MCB C 16 A, 3-pole 1x MCB C 16 A, 1-pole Input CEE plug 400 V, 32 A, 5-pole with 2 m H07RN-F 5G6 Output 3x shock-proof socket outlet 230 V, 16 A, IP44 1x CEE socket 400 V, 32 A, 5-pole 1x CEE s	Cable color	black
Rated current [A] 16 Maximum power 22 kW IP protection IP44 Protection device 1x MCB C 16 A, 3-pole 1x MCB C 16 A, 1-pole Input CEE plug 400 V, 32 A, 5-pole with 2 m H07RN-F 5G6 Output 3x shock-proof socket outlet 230 V, 16 A, IP44 1x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole Total number of sockets 5 Number of Type F sockets (230 V) 3 Number of CEE 400 V 16 A sockets 1	Cable length [m]	2
Maximum power 22 kW IP protection IP44 Protection device 1x MCB C 16 A, 3-pole 1x MCB C 16 A, 1-pole Input CEE plug 400 V, 32 A, 5-pole with 2 m H07RN-F 5G6 Output 3x shock-proof socket outlet 230 V, 16 A, IP44 1x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole Total number of Type F sockets (230 V) Number of CEE 400 V 16 A sockets 1	Rated voltage [V]	400
IP protection Protection device 1x MCB C 16 A, 3-pole 1x MCB C 16 A, 1-pole Input CEE plug 400 V, 32 A, 5-pole with 2 m H07RN-F 5G6 Output 3x shock-proof socket outlet 230 V, 16 A, IP44 1x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole Number of Type F sockets (230 V) Number of CEE 400 V 16 A sockets 1	Rated current [A]	16
Protection device 1x MCB C 16 A, 3-pole 1x MCB C 16 A, 1-pole 1x MCB C 16 A, 5-pole with 2 m H07RN-F 5G6 Output 3x shock-proof socket outlet 230 V, 16 A, IP44 1x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 1x CEE 400 V 16 A sockets 1	Maximum power	22 kW
Input CEE plug 400 V, 32 A, 5-pole with 2 m H07RN-F 5G6 Output 3x shock-proof socket outlet 230 V, 16 A, IP44 1x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole Number of Type F sockets (230 V) Number of CEE 400 V 16 A sockets 1	IP protection	IP44
Output 3x shock-proof socket outlet 230 V, 16 A, IP44 1x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole Total number of sockets 5 Number of Type F sockets (230 V) 3 Number of CEE 400 V 16 A sockets 1	Protection device	1x MCB C 16 A, 3-pole 1x MCB C 16 A, 1-pole
1x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole Total number of sockets 5 Number of Type F sockets (230 V) Number of CEE 400 V 16 A sockets 1	Input	CEE plug 400 V, 32 A, 5-pole with 2 m H07RN-F 5G6
Number of Type F sockets (230 V) 3 Number of CEE 400 V 16 A sockets 1	Output	1x CEE socket 400 V, 16 A, 5-pole
Number of CEE 400 V 16 A sockets 1	Total number of sockets	5
	Number of Type F sockets (230 V)	3
Number of CFF 400 V 32 A sockets 1	Number of CEE 400 V 16 A sockets	1
Number of CEE 400 V 32 / 1 30CRC 3	Number of CEE 400 V 32 A sockets	1

