Product Datasheet

Item No.: 60934



PRODUCT NAME **STECKY DUO 4 CEE power combination unit**

















- Robust housing made from shatterproof special plastic
- Stable metal frame with edge protection
- With large ergonomic carry handle and cable winder
- Dimensions (W x H x D): 400 x 450 x 252 mm
- IP44: protected against foreign bodies and splash-proof

Reference image

Technical data

lechnical data	
EAN	4011160609343
Weight [kg]	9
Dimensions	26x46,5x40,5 cm
Main color	black
Series	STECKY DUO
Category	CEE 400 V product range
Subcategory	STECKY CEE power combination units
Cable type	H07RN-F
Cross section [mm ²]	5G6
Cable color	black
Cable length [m]	2.1
Rated voltage [V]	400
Rated current [A]	16
Maximum power	22 kW
IP protection	IP44
Protection device	1x RCD 40 A, 30 mA, type A 1x MCB C 16 A, 3-pole 4x MCB C 16 A, 1-pole
Input	CEE plug 400 V, 32 A, 5-pole with 3.4 m H07RN-F 5G6
Output	6x shock-proof socket outlet 230 V, 16 A, IP44 (distributed over phases) 1x CEE socket 230 V, 16 A, 3-pole 1x CEE socket 400 V, 16 A, 5-pole 2x CEE socket 400 V, 32 A, 5-pole 2x USB socket 5 V / 2.1 A Phase display L1, L2, L3
Total number of sockets	11
Number of Type F sockets (230 V)	6
Number of USB ports	2
Number of CEE 400 V 16 A sockets	1
Number of CEE 400 V 32 A sockets	2



Technical data

Number of CEE 230 V sockets

1

