Product Datasheet

Item No.: 60973



PRODUCT NAME

Suspended distributor 8-way ZUGSPITZE 3 m H07RN-F 3G1,5 IP44















- Suspended distributors provide current in the correct amount right where it's needed
- Housing made from special plastic with handle or tool hook
- Includes 3 m stable galvanized steel link chain
- 230 V, 16 A
- 3 m H07RN-F 3G1,5 heavy-duty rubber power cable with shock-proof plug
- 2x 4 shock-proof socket outlets 230 V, 16 A, 2 PE with flap lids, IP44

Reference image

Technical data

EAN4011160609732Weight [kg]1.4Dimensions15x17x24 cmMain colorblackCategoryPower cubes and suspended distributorsSubcategorySuspended distributorsCable typeH07RN-FCross section [mm²]3G1,5Cable colorblackCable length [m]3Rated voltage [V]230Rated current [A]16IP protectionIP44InputShock-proof plug 230 V, 16 A, IP44Output2x 4x shock-proof socket outlet 230 V, 16 A, IP44, 3 m galvanized chain included	Total autu	
Dimensions15x17x24 cmMain colorblackCategoryPower cubes and suspended distributorsSubcategorySuspended distributorsCable typeH07RN-FCross section [mm²]3G1,5Cable colorblackCable length [m]3Rated voltage [V]230Rated current [A]16IP protectionIP44InputShock-proof plug 230 V, 16 A, IP44		4011160609732
Main colorblackCategoryPower cubes and suspended distributorsSubcategorySuspended distributorsCable typeH07RN-FCross section [mm²]3G1,5Cable colorblackCable length [m]3Rated voltage [V]230Rated current [A]16IP protectionIP44InputShock-proof plug 230 V, 16 A, IP44	kg]	1.4
Category Power cubes and suspended distributors Subcategory Suspended distributors Cable type H07RN-F Cross section [mm²] 3G1,5 Cable color black Cable length [m] 3 Rated voltage [V] 230 Rated current [A] 16 IP protection IP44 Input Shock-proof plug 230 V, 16 A, IP44	ons	15x17x24 cm
SubcategorySuspended distributorsCable typeH07RN-FCross section [mm²]3G1,5Cable colorblackCable length [m]3Rated voltage [V]230Rated current [A]16IP protectionIP44InputShock-proof plug 230 V, 16 A, IP44	or	black
Cable type H07RN-F Cross section [mm²] 3G1,5 Cable color black Cable length [m] 3 Rated voltage [V] 230 Rated current [A] 16 IP protection IP44 Input Shock-proof plug 230 V, 16 A, IP44	<i>y</i>	Power cubes and suspended distributors
Cross section [mm²] 3G1,5 Cable color black Cable length [m] 3 Rated voltage [V] 230 Rated current [A] 16 IP protection IP44 Input Shock-proof plug 230 V, 16 A, IP44	gory	Suspended distributors
Cable color black Cable length [m] 3 Rated voltage [V] 230 Rated current [A] 16 IP protection IP44 Input Shock-proof plug 230 V, 16 A, IP44	ре	H07RN-F
Cable length [m] 3 Rated voltage [V] 230 Rated current [A] 16 IP protection IP44 Input Shock-proof plug 230 V, 16 A, IP44	ction [mm²]	3G1,5
Rated voltage [V] 230 Rated current [A] 16 IP protection IP44 Input Shock-proof plug 230 V, 16 A, IP44	lor	black
Rated current [A] 16 IP protection IP44 Input Shock-proof plug 230 V, 16 A, IP44	ngth [m]	3
IP protectionIP44InputShock-proof plug 230 V, 16 A, IP44	ltage [V]	230
Input Shock-proof plug 230 V, 16 A, IP44	rrent [A]	16
	ction	IP44
Output 2x 4x shock-proof socket outlet 230 V 16 A IP44 3 m galvanized chain included		Shock-proof plug 230 V, 16 A, IP44
Ex ix shock proof socket outlet 250 V, 10 V, II VI, 5 III guivanized chair included		2x 4x shock-proof socket outlet 230 V, 16 A, IP44, 3 m galvanized chain included
Total number of sockets 8	mber of sockets	8
Number of Type F sockets (230 V) 8	of Type F sockets (230 V)	8

