

Product Datasheet

Item No.: 61377



PRODUCT NAME

Adapter set – for complete peace of mind - charger and full set of adapters: 65152, 61373, 61374, 61375, 61376 and protective bag



Reference image



- Set consists of:
- Portable electric car charger MODE 2 (art. no. 65152) CEE 32 A plug to Type 2, 400 V, max. 32 A 22 kW, adjustable charging current 10 A / 16 A / 20 A / 24 A / 32 A, length 5 m, protection class IP44, operating temperature range -25°C to +50°C
- Adapter cord E2 (art. no. 61373) 0.3 m heavy-duty rubber cable H07RN-F 3G2.5. 1st end: Shock-proof plug 230 V / 16 A, 2nd end: CEE connector, red 400 V / 32 A / 5-pole, 230 V 16 A max. 3.5 kW, IP44
- Adapter cord E4 (art. no. 61374) 0.3 m heavy-duty rubber cable H07RN-F 3G2.5, 1st end: CEE plug, blue 230 V / 16 A / 3-pole, 2nd end: CEE connector, red 400 V / 32 A / 5-pole with flap lid, 230 V 16 A max. 3.6 kW, IP44
- Adapter cord E5 (art. no. 61375) 0.3 m heavy-duty rubber cable H07RN-F 3G6. 1st end: CEE plug, blue 230 V / 32 A / 3-pole, 2nd end: CEE connector, red 400 V / 32 A / 5-pole with flap lid, 230 V 32 A max. 7.2 kW, IP44
- CEE adapter cord E6 (art. no. 61376) 0.3 m heavy-duty rubber cable H07RN-F 5G2.5, 1st end: CEE plug, red 400 V / 16 A / 5-pole, 2nd end: CEE connector, red 400 V / 32 A / 5-pole, 400 V / 16 A max. 11 kW, IP44

Technical data

EAN	4011160613777
Weight [kg]	6
Dimensions	40x32x40 cm
Main color	black
Category	E-Mobility
Subcategory	Adapter cords
Cable type	H07RN-F
Cross section [mm²]	5G2,5
Cable color	black
Cable length [m]	0.3
Rated voltage [V]	400
Rated current [A]	32
IP protection	IP44

Your partner for professional lighting and electrical products.

