

Product Datasheet

Item No.: 61517



PRODUCT NAME

FIXO 3 combination unit with panel-mounted plug for connection to the power supply



Reference image



- Robust housing made from shatterproof special plastic, including carry handle
- Compact construction, ideal for wall attachment
- FIXO housing dimensions: 280 x 280 x 118 mm
- FIXO MAX housing dimensions: 370 x 375 x 118 mm
- IP44: protected against foreign bodies and splash-proof

Technical data

EAN	4011160615177
Weight [kg]	3.43
Dimensions	13x38x28 cm
Main color	white
Series	FIXO
Category	CEE 400 V product range
Subcategory	FIXO CEE combination units
Rated voltage [V]	400
Rated current [A]	16
Maximum power	22 kW
IP protection	IP44
Protection device	1x RCD 40 A, 4-pole, 30 mA, type A 2x MCB C 16 A, 3-pole 2x MCB C 16 A, 1-pole
Input	CEE plug 400 V, 32 A, 5-pole
Output	4x shock-proof socket outlet 230 V, 16 A, IP44 2x CEE socket 400 V, 16 A, 5-pole
Total number of sockets	6
Number of Type F sockets (230 V)	4
Number of CEE 400 V 16 A sockets	2

Your partner for professional lighting and electrical products.

