

Product Datasheet

Item No.: 61519

PRODUCT NAME

FIXO 12D combination unit prepared for hard-wired connection of cables up to 5x16



Reference image



- Robust housing made from shatterproof special plastic, including carry handle
- Compact construction ideal for wall attachment
- With high-quality, sturdy main cable branch terminal for electrical installations
- Including two stepped nipples for sealing the connected cable
- FIXO housing dimensions: 280 x 280 x 118 mm
- FIXO MAX housing dimensions: 370 x 375 x 118 mm
- IP44: protected against foreign bodies and splash-proof

Technical data

EAN	4011160615191
Weight [kg]	3.9
Dimensions	13x38x28 cm
Main color	white
Series	FIXO
Category	CEE 400 V product range
Subcategory	FIXO CEE combination units
Rated voltage [V]	400
Rated current [A]	16
IP protection	IP44
Protection device	1x RCD 40 A, 4-pole, 30 mA, type A 2x MCB C 16 A, 1-pole 1x MCB C 16 A, 3-pole 1x MCB C 32 A, 3-pole
Input	Prepared for hard-wired connection of NYM-J up to max. 5x10
Output	4x shock-proof socket outlet 230 V, 16 A, IP44 1x CEE socket 400 V, 16 A, 5-pole 2x CEE socket 400 V, 32 A, 5-pole
Total number of sockets	7
Number of Type F sockets (230 V)	4
Number of CEE 400 V 16 A sockets	1
Number of CEE 400 V 32 A sockets	2

Your partner for professional lighting and electrical products.