## **Product Datasheet**

Item No.: 61524



PRODUCT NAME

## FIXO 6 MAX combination unit with panel-mounted plug for connection to the power supply













- Robust housing made from shatterproof special plastic, including carry handle
- Compact construction, ideal for wall attachment
- FIXO housing dimensions: 280 x 280 x 118 mm
- FIXO MAX housing dimensions: 370 x 375 x 118 mm
- IP44: protected against foreign bodies and splash-proof

Reference image

## **Technical data**

Weight [kg]     5       Dimensions     13x44x37 cm       Main color     white       Series     FIXO       Category     CEE 400 V product range       Subcategory     FIXO CEE combination units       Rated voltage [V]     400       Rated current [A]     32       Maximum power     22 kW       IP protection     IP44       Protection device     12 k RCD 40 A, 4-pole, 30 mA, type A 2x MCB C 16 A, 3-pole 3x MCB C 16 A, 1-pole       Input     CEE plug 400 V, 32 A, 5-pole       Output     2x Schock-proof socket outlet 230 V, 16 A, IP44 2x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 16 A, 5-pole 2x USB socket 5 V / 2.1 A       Total number of sockets     9       Number of Type F sockets (230 V)     5       Number of USB ports     2       Number of CEE 400 V 16 A sockets     2	recrimical data	
Dimensions13x44x37 cmMain colorwhiteSeriesFIXOCategoryCEE 400 V product rangeSubcategoryFIXO CEE combination unitsRated voltage [V]400Rated current [A]32Maximum power122 kWIP protectionIP44Protection device1x RCD 40 A, 4-pole, 30 mA, type A 2x MCB C 16 A, 3-pole 3x MCB C 16 A, 1-poleInputCEE plug 400 V, 32 A, 5-poleOutput5x shock-proof socket outlet 230 V, 16 A, IP44 2x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-poleTotal number of sockets9Number of Type F sockets (230 V)5Number of USB ports2Number of CEE 400 V 16 A sockets2	EAN	4011160615245
Main color  white  Series  FIXO  Category  CEE 400 V product range  Subcategory  FIXO CEE combination units  Rated voltage [V]  400  Rated current [A]  32  Maximum power  22 kW  IP protection  IP44  Protection device  1x RCD 40 A, 4-pole, 30 mA, type A 2x MCB C 16 A, 3-pole 3x MCB C 16 A, 1-pole  Input  CEE plug 400 V, 32 A, 5-pole  Output  5x shock-proof socket outlet 230 V, 16 A, IP44 2x CEE socket 400 V, 32 A, 5-pole 3x USB socket 5 V / 2.1 A  Total number of Sockets  9  Number of Type F sockets (230 V)  Number of USB ports  2  Number of CEE 400 V 16 A sockets  2	Weight [kg]	5
Series FIXO Category CEE 400 V product range Subcategory FIXO CEE combination units Rated voltage [V] 400 Rated current [A] 32 Maximum power 22 kW IP protection IP44 Protection device 1x RCD 40 A, 4-pole, 30 mA, type A 2x MCB C 16 A, 3-pole 3x MCB C 16 A, 1-pole Input CEE plug 400 V, 32 A, 5-pole 3x MCB C 16 A, 1-pole Output 5x shock-proof socket outlet 230 V, 16 A, IP44 2x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 16 A, 5-pole 2x USB socket 5 V / 2.1 A Total number of sockets  PNumber of Type F sockets (230 V) Number of USB ports  2 Number of CEE 400 V 16 A sockets 2	Dimensions	13x44x37 cm
Category  CEE 400 V product range  Subcategory  FIXO CEE combination units  Rated voltage [V]  400  Rated current [A]  32  Maximum power  1P protection  IP44  Protection device  1x RCD 40 A, 4-pole, 30 mA, type A 2x MCB C 16 A, 3-pole 3x MCB C 16 A, 1-pole  Input  CEE plug 400 V, 32 A, 5-pole 3x MCB C 16 A, 5-pole 1x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 2x USB socket 5 V / 2.1 A  Total number of sockets  9  Number of Type F sockets (230 V)  Number of USB ports  2  Number of CEE 400 V 16 A sockets  2	Main color	white
Subcategory  FIXO CEE combination units  Rated voltage [V] 400  Rated current [A] 32  Maximum power 22 kW  IP protection  IP44  Protection device 1x RCD 40 A, 4-pole, 30 mA, type A 2x MCB C 16 A, 3-pole 3x MCB C 16 A, 3-pole 3x MCB C 16 A, 1-pole  Input CEE plug 400 V, 32 A, 5-pole  Output 2x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 2x USB socket 5 V / 2.1 A  Total number of sockets 9  Number of Type F sockets (230 V) 5  Number of USB ports 2  Number of CEE 400 V 16 A sockets 2	Series	FIXO
Rated voltage [V] 400  Rated current [A] 32  Maximum power 22 kW  IP protection IP44  Protection device 1x RCD 40 A, 4-pole, 30 mA, type A 2x MCB C 16 A, 3-pole 3x MCB C 16 A, 1-pole  Input CEE plug 400 V, 32 A, 5-pole  Output 2x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 2x USB socket 5 V / 2.1 A  Total number of Sockets 9  Number of Type F sockets (230 V) 5  Number of USB ports 2  Number of CEE 400 V 16 A sockets 2	Category	CEE 400 V product range
Rated current [A]32Maximum power22 kWIP protectionIP44Protection device1x RCD 40 A, 4-pole, 30 mA, type A 2x MCB C 16 A, 3-pole 3x MCB C 16 A, 1-poleInputCEE plug 400 V, 32 A, 5-poleOutput5x shock-proof socket outlet 230 V, 16 A, IP44 2x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 1x CEE socket 5 V / 2.1 ATotal number of sockets9Number of Type F sockets (230 V)5Number of USB ports2Number of CEE 400 V 16 A sockets2	Subcategory	FIXO CEE combination units
Maximum power  IP protection  IP44  Protection device  1x RCD 40 A, 4-pole, 30 mA, type A 2x MCB C 16 A, 3-pole 3x MCB C 16 A, 1-pole  Input  CEE plug 400 V, 32 A, 5-pole  5x shock-proof socket outlet 230 V, 16 A, IP44 2x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 2x USB socket 5 V / 2.1 A  Total number of sockets  9  Number of Type F sockets (230 V)  Number of USB ports  2  Number of CEE 400 V 16 A sockets  2	Rated voltage [V]	400
IP protection  Protection device  1x RCD 40 A, 4-pole, 30 mA, type A 2x MCB C 16 A, 3-pole 3x MCB C 16 A, 1-pole  Input  CEE plug 400 V, 32 A, 5-pole  Sx shock-proof socket outlet 230 V, 16 A, IP44 2x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 2x USB socket 5 V / 2.1 A  Total number of sockets  9  Number of Type F sockets (230 V)  Number of USB ports  2  Number of CEE 400 V 16 A sockets  2	Rated current [A]	32
Protection device  1 x RCD 40 A, 4-pole, 30 mA, type A 2x MCB C 16 A, 3-pole 3x MCB C 16 A, 1-pole  Input  CEE plug 400 V, 32 A, 5-pole  5x shock-proof socket outlet 230 V, 16 A, IP44 2x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 2x USB socket 5 V / 2.1 A  Total number of sockets  9  Number of Type F sockets (230 V)  5 Number of USB ports  2  Number of CEE 400 V 16 A sockets  2	Maximum power	22 kW
2x MCB C 16 A, 3-pole 3x MCB C 16 A, 1-pole  Input  CEE plug 400 V, 32 A, 5-pole  5x shock-proof socket outlet 230 V, 16 A, IP44 2x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 2x USB socket 5 V / 2.1 A  Total number of sockets  9  Number of Type F sockets (230 V)  5 Number of USB ports  2  Number of CEE 400 V 16 A sockets  2	IP protection	IP44
Output  5x shock-proof socket outlet 230 V, 16 A, IP44 2x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 2x USB socket 5 V / 2.1 A  Total number of sockets  9  Number of Type F sockets (230 V)  5  Number of USB ports  2  Number of CEE 400 V 16 A sockets  2	Protection device	2x MCB C 16 A, 3-pole
2x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole 2x USB socket 5 V / 2.1 A  Total number of sockets 9 Number of Type F sockets (230 V) 5 Number of USB ports 2 Number of CEE 400 V 16 A sockets 2	Input	CEE plug 400 V, 32 A, 5-pole
Number of Type F sockets (230 V) 5 Number of USB ports 2 Number of CEE 400 V 16 A sockets 2	Output	2x CEE socket 400 V, 16 A, 5-pole 1x CEE socket 400 V, 32 A, 5-pole
Number of USB ports 2 Number of CEE 400 V 16 A sockets 2	Total number of sockets	9
Number of CEE 400 V 16 A sockets 2	Number of Type F sockets (230 V)	5
	Number of USB ports	2
Number of CEE 400 V 32 A sockets 1	Number of CEE 400 V 16 A sockets	2
	Number of CEE 400 V 32 A sockets	1

