Product Datasheet

Item No.: 61757



PRODUCT NAME

ROCO 1 energy meter, 1-phase 3 m H07BQ-F 3G2,5



Reference image













- Approved for insurance claims, campsites, construction sites and agricultural applications
- Integrated energy meter in a compact housing made of shatter-proof special plastic with a window for reading the analogue display
- MID-compliant and suitable for billing purposes
- AC meter, 1-phase
- Accuracy class B
- Analogue display: 5+1 digits, readable at any time
- Display for max. 99,999.9 kWh
- Non-resettable analogue display
- 230 V, 16 A, max. 3.5 kW, 50 Hz
- Rated current 0.25-5 A (max. 45 A)
- Operating temperature from -25°C to +55°C
- SDM 120 A, 230 V, 50 Hz
- IP44: protected against foreign bodies and splash-proof
- 1.5 m H07BQ-F 3G2.5 blue polyurethane cable with
- shock-proof plug and shock-proof connector with protective cap
- Including sturdy strap for hanging
- 230 V, 16 A, max. 3.5 kW

Technical data

reciliicai data	
EAN	4011160617577
Weight [kg]	1
Dimensions	35x10x30 cm
Main color	black
Series	ROCO
Category	Energy meters and inrush current limiters
Subcategory	Energy meters
Cable type	H07BQ-F
Cross section [mm²]	3G2,5
Cable color	blue
Cable length [m]	3
Rated voltage [V]	230
Rated current [A]	16
Maximum power	3500 W
IP protection	IP44
Input	Shock-proof plug 230 V, 16 A, IP44
Output	1x shock-proof socket outlet 230 V, 16 A, IP44
Total number of sockets	1
Number of Type F sockets (230 V)	1

