

Product Datasheet

Item No.: 61758



PRODUCT NAME

ROCO 3 energy meter, 1-phase, with voltage indicator 3 m H07BQ-F 3G2,5



Reference image



- Approved for insurance claims, campsites, construction sites and agricultural applications
- Integrated energy meter in a compact housing made of shatter-proof special plastic with a window for reading the analogue display
- MID-compliant and suitable for billing purposes
- AC meter, 1-phase
- Accuracy class B
- Analogue display: 5+1 digits, readable at any time
- Display for max. 99,999.9 kWh
- Non-resettable analogue display
- 230 V, 16 A, max. 3.5 kW, 50 Hz
- Rated current 0.25-5 A (max. 45 A)
- Operating temperature from -25°C to +55°C
- SDM 120 A, 230 V, 50 Hz
- IP44: protected against foreign bodies and splash-proof
- 1.5 m H07BQ-F 3G2.5 blue polyurethane cable with
- 230 V, 16 A, 3-pole CEE with 'powerlight' voltage indicator, and 230 V, 16 A, 3-pole CEE connector with flap lid and 'powerlight' voltage indicator
- If the red LED on plug and connector lights up, the cable is live.
- Including sturdy strap for hanging
- 230 V, 16 A, max. 3.5 kW

Technical data

EAN	4011160617584
Weight [kg]	1
Dimensions	35x10x30 cm
Main color	blue
Series	ROCO PowerLight
Category	Energy meters and inrush current limiters
Subcategory	Energy meters
Cable type	H07BQ-F
Cross section [mm²]	3G2,5
Cable color	blue
Cable length [m]	3
Rated voltage [V]	230
Rated current [A]	16
Maximum power	3500 W
IP protection	IP44
Input	CEE plug 230 V, 16 A, 3-pole with 'PowerLight' voltage indicator
Output	1x CEE connector 230 V, 16 A, 3-pole with 'PowerLight' voltage indicator
Total number of sockets	1
Number of Type F sockets (230 V)	1
Number of CEE 230 V sockets	1

Your partner for professional lighting and electrical products.

