

# Product Datasheet

Item No.: 70430

PRODUCT NAME

## Retractable spiral cord 1 m elastic up to 5 m H07BQ-F 3G1,5 OG



- IP44: protected against foreign bodies and splash-proof
- Open cable end: approx. 50 mm stripped with wire-end ferrules
- Plug end: with shock-proof plug
- Retractable polyurethane spiral cord
- Flexibly elastic
- Retracts again automatically
- 230 V, 16 A

Reference image

### Technical data

|                                  |                                                               |
|----------------------------------|---------------------------------------------------------------|
| EAN                              | 4011160704307                                                 |
| Weight [kg]                      | 0.6                                                           |
| Dimensions                       | 18x8x20 cm                                                    |
| Main color                       | orange                                                        |
| Category                         | Power cords                                                   |
| Subcategory                      | Power cords                                                   |
| Cable type                       | H07BQ-F                                                       |
| Cross section [mm <sup>2</sup> ] | 3G1,5                                                         |
| Cable color                      | orange                                                        |
| Cable length [m]                 | 5                                                             |
| Rated voltage [V]                | 230                                                           |
| Rated current [A]                | 16                                                            |
| IP protection                    | IP44                                                          |
| Input                            | Shock-proof plug 230 V, 16 A, IP44                            |
| Output                           | Open cable end: approx. 35 mm stripped with wire-end ferrules |
| Number of cores                  | 3                                                             |

Your partner for professional lighting and electrical products.