

Product Datasheet

Item No.: 845303



PRODUCT NAME

PRCD extension 1-way 30 mA 3 m H07RN-F 3G2,5 IP44 "F"



- IP44: protected against foreign bodies and splash-proof
- Residual current is detected in a split second, and the supply of current interrupted. The PRCD-S therefore provides reliable protection against electric shock and has been approved by the employer's liability insurance association.
- PLEASE NOTE: The switch-on button on the PRCD-S must be actuated using a bare hand in order for the protective function to work. Do not use with gloves!
- Plastic housing with function display and trip test button
- Rated residual current: 30 mA
- Trigger time less than 30 ms
- IP55: protected against dust and jet water
- 2x 1.5 m H07BQ-F 3G2,5 heavy-duty polyurethane power cable with shock-proof plug
- With PRCD-S inline RCD (article number 45305)
- 230 V, 16 A, max. 3,500 W

Reference image

Technical data

EAN	4059948000180
Weight [kg]	0.8
Dimensions	17x17x8 cm
Main color	black
Series	PRCD
Category	Personal protection range
Subcategory	PRCD range
Cable type	H07RN-F
Cross section [mm²]	3G2,5
Cable color	black
Cable length [m]	3
Rated voltage [V]	230
Rated current [A]	16
Maximum power	3500 W
IP protection	IP44
Protection device	PRCD inline RCD 30 mA IP66 (art. no. 45223)
Input	Shock-proof plug 230 V, 16 A, IP44
Output	1x shock-proof connector with protective cap 230 V, 16 A, IP44 "F"
Total number of sockets	1
Number of Type E sockets (230 V)	1
mA	30

Your partner for professional lighting and electrical products.



as – Schwabe GmbH Merkurstraße 10 D – 72184 Eutingen Tel. +49 7457 9 48 53 0 office@as-schwabe.de www.as-schwabe.com

Created 21.10.2025. All proprietary rights and the right to make technical changes are reserved. Reproduction is permitted only with the prior consent of as – Schwabe GmbH.