

Product Datasheet

Item No.: 845458

PRODUCT NAME

PRCD-S extension 1-way IP44 30 mA 3 m H07BQ-F 3G2,5 IP44 "F"



Reference image



- IP44: protected against foreign bodies and splash-proof
- Residual current is detected in a split second, and the supply of current interrupted. The PRCD-S therefore provides reliable protection against electric shock and has been approved by the employer's liability insurance association.
- PLEASE NOTE: The switch-on button on the PRCD-S must be actuated using a bare hand in order for the protective function to work. Do not use with gloves!
- Plastic housing with function display and trip test button
- Rated residual current: 30 mA
- Trigger time less than 30 ms
- IP55: protected against dust and jet water
- 2x 1.5 m H07BQ-F 3G2,5 heavy-duty polyurethane power cable with shock-proof plug
- With PRCD-S inline RCD (article number 45305)
- 230 V, 16 A, max. 3,500 W

Technical data

EAN	4059948004379
Weight [kg]	0.9
Dimensions	26x6x30 cm
Main color	orange
Series	PRCD
Category	Personal protection range
Subcategory	PRCD-S range
Cable type	H07BQ-F
Cross section [mm ²]	3G2,5
Cable color	orange
Cable length [m]	3
Rated voltage [V]	230
Rated current [A]	16
Maximum power	3500 W
IP protection	IP44
Protection device	PRCD-S inline RCD 30 mA IP55 (art. no. 45305)
Input	Shock-proof plug 230 V, 16 A, IP44
Output	1x shock-proof connector with protective cap 230 V, 16 A, IP44 "F"
Total number of sockets	1
Number of Type E sockets (230 V)	1
mA	30

Your partner for professional lighting and electrical products.