

# Product Datasheet

Item No.: 846344

PRODUCT NAME

## Optiline mobile LED floodlight 24 W "F" - 2500 lm



Reference image



- LEDs with a lifespan of over 40,000 hours
- Color temperature: 4,000 K (neutral white)
- LED beam angle: 100°
- Color rendering index: CRI > 80
- With polycarbonate diffuser plate
- Extremely slimline floodlight housing made of special plastic and lockable fixing holder
- Power cord and diffuser plate cannot be replaced
- Connection: 220-240 V/50 Hz
- 3 m heavy-duty rubber cable H07RN-F 3G1.5 with shock-proof plug
- IP54: protected against dust and splash-proof

### Technical data

|                                  |                                                                    |
|----------------------------------|--------------------------------------------------------------------|
| EAN                              | 4059948004461                                                      |
| Weight [kg]                      | 1.54                                                               |
| Dimensions                       | 10x24,8x31 cm                                                      |
| Main color                       | black                                                              |
| Series                           | Optiline                                                           |
| Category                         | Lighting                                                           |
| Subcategory                      | Optiline floodlight series                                         |
| Cable type                       | H07RN-F                                                            |
| Cross section [mm²]              | 3G1,5                                                              |
| Cable color                      | black                                                              |
| Cable length [m]                 | 3                                                                  |
| Rated voltage [V]                | 230                                                                |
| Rated current [A]                | 16                                                                 |
| Power [W]                        | 24                                                                 |
| IP protection                    | IP54                                                               |
| Input                            | Shock-proof plug 230 V, 16 A, IP44 with 3 m H07RN-F 3G1,5          |
| Output                           | 1x shock-proof connector with protective cap 230 V, 16 A, IP44 "F" |
| Light color [K]                  | 4000                                                               |
| Luminous flux [lm]               | 2500                                                               |
| Total number of sockets          | 1                                                                  |
| Number of Type E sockets (230 V) | 1                                                                  |

Your partner for professional lighting and electrical products.