

Product Datasheet

Item No.: 846371



PRODUCT NAME
360° LED light column 100 W "F" - 8000 lm



- Optimum light distribution due to 360° illumination
- 296x SMD2835 LED encased in protective polycarbonate column
- Folding suspension hook at the top of the column
- Stable, 3-legged frame made of powder-coated metal
- Span of tripod: 1.05 m
- Height: 1.42 m
- On frame 1 shock-proof socket outlet 230 V~/16 A/ max. 3500 W, IP54
- 3 m heavy-duty rubber cable H07RN-F 3G1.5 with shock-proof plug
- Connection: 230 V / 16 A / max. 3500 W / 50-60 Hz
- IP44: protected against foreign bodies and splash-proof

Reference image

Technical data

EAN	4059948004812
Weight [kg]	5
Dimensions	25,5x145x26,5 cm
Main color	black
Category	Lighting
Subcategory	360° rotating beacon
Cable type	H07RN-F
Cross section [mm²]	3G1,5
Cable color	black
Cable length [m]	3
Rated voltage [V]	230
Rated current [A]	16
Power [W]	100
IP protection	IP44
Input	Shock-proof plug 230 V, 16 A, IP44 with 1,8 m H07RN-F 3G1,5
Output	1x shock-proof connector with protective cap 230 V, 16 A, IP54 "F"
Light color [K]	4000
Luminous flux [lm]	8000
Total number of sockets	1
Number of Type E sockets (230 V)	1

Your partner for professional lighting and electrical products.

